

**HDC housing;bulkhead housing
FRONTCOM GH KEY**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The FrontCom® **Classic frames can be freely combined with the corresponding inserts.**

General ordering data

Order No.	187920000
Type	FRONTCOM GH KEY
Version	Lockable housing
GTIN (EAN)	4032248474318
Qty.	1 pc(s).

**HDC housing; bulkhead housing
FRONTCOM GH KEY**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Length	33 mm	Width	101 mm
Height	136 mm	Net weight	202 g

Temperatures

Operating temperature	-20 °C...+80 °C
-----------------------	-----------------

Technical specifications for D-Sub

Operating temperature (D-Sub)	
-------------------------------	--

Technical specifications for RJ45 coupling

Operating temperature (RJ45 coupling)	
---------------------------------------	--

Technical specifications for RJ45 module

Operating temperature (RJ45 module)	
-------------------------------------	--

Technical specifications for socket

Operating temperature (plug socket)	Pollution severity	3
-------------------------------------	--------------------	---

Technical data

Height	136 mm	Length	33 mm
Operating temperature	-20 °C...+80 °C	Operating temperature, max.	80 °C
Operating temperature, min.	-20 °C	Version	Lockable housing
Material	PPE	UL 94 flammability rating	V-1
Colour	Grey	Storage temperature, max.	80 °C
Storage temperature, min.	-20 °C	Protection degree	IP 65
Pollution severity	3		

Classifications

ETIM 2.0	EC000456	ETIM 3.0	EC000456
UNSPSC	31-16-23-03	eClass 5.1	27-18-92-17
eClass 6.2	27-18-92-17	eClass 7.1	27-18-92-17

Approvals

Approvals	
ROHS	Conform

**HDC housing; bulkhead housing
FRONTCOM GH KEY**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings**Drawing**