

Apr.1.2017 Copyright 2017 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
<b>APPLICATION STANDARD</b>									
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO +85 °C			STORAGE TEMPERATURE RANGE	--- °C TO --- °C			
	VOLTAGE	200V AC			OPERATING HUMIDITY RANGE	--- % TO --- %			
	CURRENT	2 A			APPLICABLE CABLE	AWG#26~36			
<b>SPECIFICATIONS</b>									
ITEM		TEST METHOD			REQUIREMENT			QT/AT	
<b>CONSTRUCTION</b>									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING			O O	
MARKING		CONFIRMED VISUALLY						O O	
<b>ELECTRICAL CHARACTERISTICS</b>									
CONTACT RESISTANCE		mA (DC OR 1000 Hz)			mΩ MAX.			-- --	
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		mV MAX, mA (DC OR 1000 Hz)			mΩ MAX.			-- --	
INSULATION RESISTANCE		500 V DC			1000 MΩ MIN.			O --	
VOLTAGE PROOF		650 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN			O --	
<b>MECHANICAL CHARACTERISTICS</b>									
CONTACT INSERTION AND EXTRACTION FORCES		BY STEEL GAUGE.			INSERTION FORCE: N MAX. EXTRACTION FORCE: N MIN.			-- --	
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE: N MAX. WITHDRAWAL FORCE: N MIN.			-- --	
MECHANICAL OPERATION		TIMES INSERTION AND EXTRACTIONS.			1) CONTACT RESISTANCE: mΩ MAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.			-- --	
VIBRATION		FREQUENCY: TO Hz, AMPLITUDE: mm, - m/s <sup>2</sup> AT h FOR DIRECTIONS.			1) NO ELECTRICAL DISCONTINUITY OF μs 2) CONTACT RESISTANCE: - mΩ MAX. 3) NO DAMAGE, CRACK AND LOOSENESS OF PART.			-- --	
SHOCK		m/s <sup>2</sup> DURATION OF PULSE ms AT TIMES FOR DIRECTIONS.						-- --	
<b>ENVIRONMENTAL CHARACTERISTICS</b>									
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90~95 %, 96 h.			1) <del>CONTACT RESISTANCE: mΩ MAX.</del> 2) INSULATION RESISTANCE: 1000 MΩ MIN.			O --	
RAPID CHAGE OF TEMPERTURE		TEMPERTURE-55→15~35→ 85→15~35°C TIME 30→10~15 →30→10~15 min. UNDER 5 CYCLES.			3) NO DAMAGE, CRACK AND LOOSENESS OF PART.			O --	
DAMP HEAT,CYCLIC		EXPOSED AT TO °C, TO % TOTAL CYCLES( h).			1) CONTACT RESISTANCE: mΩ MAX. 2) INSULATION RESISTANCE: MΩ MIN.(AT HIGH HUMIDITY) 3) INSULATION RESISTANCE: MΩ MIN.(AT DRY) 4) NO DAMAGE, CRACK AND LOOSENESS OF PART.			-- --	
DRY HEAT		EXPOSED AT °C, h.			1) CONTACT RESISTANCE: mΩ MAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.			-- --	
CORROSION SALT MIST		EXPOSED IN % SALT WATER SPRAY FOR h.			1) CONTACT RESISTANCE: mΩ MAX. 2) NO HEAVY CORROSION.			-- --	
HYDROGEN SULPHIDE		EXPOSED IN PPM FOR h. (TEST STANDARD:JEIDA-38)						-- --	
SULPHUR DIOXIDE		EXPOSED IN PPM FOR h. (TEST STANDARD:JEIDA-39)						-- --	
RESISTANCE TO SOLDERING HEAT		SOLDER TEMPERATURE, °C FOR IMMERSION,DURATION, s.(MIL-STD-202)			NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL.			-- --	
SOLDRABILITY		SOLDERED AT SOLDER TEMPERATURE, °C FOR IMMERSION DURATION, s.(MIL-STD-202)			A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.			-- --	
REMARKS				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
UNLESS OTHERWISE SPECIFIED, REFER TO MIL-STD-1364				J. Jankala 97.10.01	J. Jankala 97.10.01	H. Obara 97.10.02	M. Yamaguchi 97.10.03		
NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST O: APPLICABLE TEST									
<b>HRS</b> HIROSE ELECTRIC CO.,LTD.		SPECIFICATION SHEET			PART NO. A3B-44D-2C				
CODE NO.(OLD)		DRAWING NO.		CODE NO.		1			
CL		ELC4- 082333		CL 621 - 0330 - 5		1			

TO
PCK

