



PERFORMANCE CHARACTERISTICS

CURRENT RATING: 1.5 A AT 20°C (FULLY LOADED)
 1 A AT 70°C (FULLY LOADED)
 RATED VOLTAGE: 500 V AC (CONT /CONT)
 OPERATING TEMPERATURE : -55°C TO 125°C
 CONTACT RESISTANCE : 20 mΩ MAX
 INSERTION FORCE: 0.75N MAX/CONT
 EXTRACTION FORCE : 0.15N MIN /CONT
 INSULATION RESISTANCE: 10⁴ MΩ MIN

NOTES

- 1. "LF" LEAD FREE INDICATOR; LF=LEAD FREE
- 1. "P" PERFORMANCE LEVEL INDICATOR (REF DWG NO. BSC201844003)
- 2. THIS PRODUCT IS CSA APPROVED
THIS PRODUCT IS UL RECOGNIZED.
- 3. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING: BSA201572001
- 4. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.

rev	ecn no	dr	date
A	DG07-0238	KL	06/07/07
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com		surface <input checked="" type="checkbox"/>	tolerance std	projection	MM
		TOLERANCES UNLESS OTHERWISE SPECIFIED			
Dr	Kason Luo	06/07/07	ANGULAR	0.X ± 0.20	size A4
Eng	Kason Luo	06/07/07	LINEAR	0.XX ± 0.10	Scale 2.000
Chr	Gary Hsieh	06/07/07	0° ± 1°	0.XXX ± 0.05	ECN
Appr	Joseph Hsia	06/07/07	Product family	MILLIPACS	Spec ref



title	MPACS 5+2R RA RCP CONN TYPE B	dwg no	BSC201444064	Rev.	A
catalog	HM2R02PA5107	customer copy	sheet 1 of 1		