

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
APPLICABLE STANDARD									
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO +85 °C			STORAGE TEMPERATURE RANGE	-30 °C TO +85 °C			
	VOLTAGE	—			OPERATING HUMIDITY RANGE	— % TO — %			
	CURRENT	—			APPLICABLE CABLE	—			
SPECIFICATIONS									
ITEM		TEST METHOD			REQUIREMENTS			QT AT	
CONSTRUCTION									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			X	X
MARKING		CONFIRMED VISUALLY.						X	X
REMARKS									
REMARKS					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
					<i>M. Shingama</i> 07.10.16	<i>M. Shingama</i> 07.10.16	<i>K. Shikawa</i> 07.10.16	<i>[Signature]</i> 07.10.16	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test									
HRS HIROSE ELECTRIC CO., LTD.				SPECIFICATION SHEET			PART NO. ZX64-SLDB		
CODE NO.(OLD) CL		DRAWING NO. ELC4-126576			CODE NO. CL242-0049-8			1	1

TO