

Fuse - VF-SI/TR5/6,3AT - 2901000

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in fuse (TR5[®]), nominal current: 6.3 A, tripping characteristic: slow-blow (T), packing volume per unit: 8 pcs.

The figure shows the 1AT version

Product Features



Key commercial data

Packing unit	1 pc
Custom tariff number	85361010
Country of origin	Germany

Technical data

General

Nominal voltage U_N	≤ 250 V AC/DC
Fuse	6.3 A Slow-blow

Classifications

eCl@ss

eCl@ss 4.0	27142098
eCl@ss 4.1	27142098
eCl@ss 5.0	27142007
eCl@ss 5.1	27142001
eCl@ss 6.0	27142001
eCl@ss 7.0	27142001

ETIM

ETIM 2.0	EC000313
ETIM 3.0	EC000035

Fuse - VF-SI/TR5/6,3AT - 2901000

Classifications

ETIM

ETIM 4.0	EC000035
ETIM 5.0	EC001423

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421