



DESIGNED FOR USE WITH	.085 S.R.
CABLE ENTRY DIAMETER	MINIMUM
HOUSING	.088
CONTACT	.024

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₁	REVISED	8/18/96	[Signature]

COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATED PER QQ-P-35
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

COMPONENT	MATERIAL	FINISH
-----------	----------	--------

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY	DATE	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	CHECKED BY	3/26/81	
	APPD BY	3/27/81	

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE "OSSM" STRAIGHT CABLE PLUG - DIRECT SOLDER ATTACHMENT (40 GHz)	
	NO. A.P. 408-04776 (14-001)	SIZE B	REV 01 ₁
		SCALE 10:1	SHEET 1 OF 1

.XXX = in
XX.X = mm (REF)