




APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	 85%MAX	APPLICABLE CABLE	CABLE DIAMETER : φ5.8~6.8
	VOLTAGE		CURRENT	



SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----



CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X
 DELETED				

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 2	DIS-E-003060	TM. ONO	KN. ICHIKAWA	09.12.14

REMARK   THIS PRODUCT SHALL BE MATED WITH DH3*17S, IT APPLIES TO DH3*B-17S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402.	APPROVED	AO. SUZUKI	09.04.16
	CHECKED	MO. SHIMOYAMA	09.04.16
	DESIGNED	TS. ITO	09.04.16
	DRAWN	TS. ITO	09.04.16

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-126586-00
--	-------------	----------------

	SPECIFICATION SHEET	PART NO.	DH-17-CV1B	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0009-6-00	 1/1