




SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
DN	OFF	(DN)
2-3-5-6	OPEN	2-1-5-4

(DN) = MOMENTARY

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 5A @120VAC or 28VDC: 2A @250VAC
5. FIXED TERM. & MOVING CONTACT: COPPER ALLOY W/SILVER
6. ELECTRICAL LIFE: 40,000 make-and-break cycles at full load.
7. INSULATION RESISTANCE: 1,000M ohm min.
8. DIELECTRIC STRENGTH: 1,000V RMS @sea level.
9. OPERATING TEMP.: -30°C to +85°C.
10. ▲ DENOTES CRITICAL PARAMETER.
11. 2002/95/EC (ROHS) COMPLIANT



REV.	ECN No.	DESCRIPTION	DATE	CHKD
B	17122	FIXED TERMINALS, NOTES	3/20/07	TN
A	13602	RELEASED FOR PRODUCTION	11/17/03	AR

TITLE	SCALE	DATE	DR	DWG	REV
100AWDP5T1B4M6QE	2:1	3/20/07	TN	T102511	B



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED