

# 3M Flatback Tape 2517

Technical Data

June, 2015

---

**Product Description** 3M™ Flatback Tape 2517 is a general purpose tape for splicing liner boards, roll tabbing, core starting, bundling, holding, and package sealing applications.

---

Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Kraft paper	Rubber	Medium brown	55 m (60 yds.)

---

\*Available in metric widths (e.g., 24 mm corresponds to 1 inch)

---

## Typical Physical Properties

**Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	78 oz./in. width (85 N/100 mm)	D-3330
Tensile Strength:	35 lbs./in. width (543 N/100 mm)	D-3759
Elongation at Break:	2%	D-3759
Tape Thickness:	6.5 mils (0.16 mm)	D-3652
Temperature Use Range:	Up to 300°F (149°C)	

---

## Features

- Has good backing strength and is resistant to moist conditions.
- Can be machine dispensed.
- Can withstand a bake cycle up to 300°F (149°C) for 30 minutes.
- Can be qualified to meet Commercial Item Description CID-A-A-883A, Type II and ASTM-D6123, Type II.

---

## Application Ideas

- Ideal for liner board splicing and as a general purpose tape for bundling, holding and packaging applications.

# 3M™ Flatback Tape

2517

---

**Storage** Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

---

**Shelf Life** To obtain best performance, use this product within one year from date of shipment.

---

**Technical Information** The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

---

**Product Use** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

---

**Warranty, Limited Remedy, and Disclaimer** Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

---

**Limitation of Liability** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

**3M**  
Industrial Business  
Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
800-362-3550 • 877-369-2923 (Fax)  
www.3M.com/industrial



Recycled Paper  
40% pre-consumer  
10% post-consumer

3M is a trademark of 3M Company  
Printed in U.S.A.  
©3M 2015 (6/15)