

Specification Sheet

Part Number: 156-00876



Outside Serrated Cable Tie & Edge Clip, 8.0" Long, EC22, 1–3 mm Panel, 50lb, PA66HS, Black, 500/pkg

Article Number	156-00876
Type	T50ROSEC22
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.• Edge Clip provides low insertion force and high extraction force ideal for assembly environments.• Two piece assembly allows the mount to slide along the strap ensuring proper orientation.• Cable tie is outside serrated to reduce bundle chafing.
Quantity Per	bag

Product Description

The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.

Short Description

Outside Serrated Cable Tie & Edge Clip, 8.0" Long, EC22, 1–3 mm Panel, 50lb, PA66HS, Black, 500/pkg

Global Part Name

T50ROSEC22-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

8.0

Length L (Metric)

200

Fixation Method

EdgeClip, sideways, assembled, 2 piece

Identification Plate Position

none

Releasable Closure

No

Variant

Outside Serrated

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.20

Bundle Diameter Min (Metric)

1.0

Bundle Diameter Max (Imperial)

2.0

Bundle Diameter Max (Metric)

45.0

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Height H (Imperial)	0.05
Height H (Metric)	1.3
Panel Thickness Min(Imperial)	0.04
Panel Thickness Max(Imperial)	0.12
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	3.0
Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS PA66HS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	500

Package Quantity (Metric)

500

Customs Number

3926909987

Weight (Metric)

2052