

Specification Sheet

Part Number: T120S0PPH4



Heavy Duty Cable Tie, 8.9" Long, 60lb Tensile Strength, PP, Black, 500/pkg

Article Number	111-12827
Type	T120S
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Polypropylene cable ties provide excellent resistance to chemicals and salts.• Inside serrations allow for strong hold on cables and wire bundles.• Head design provides high tensile strength with very low insertion force.• Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description

HellermannTyton's polypropylene cable ties offer added resistance to most chemicals. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Heavy Duty Cable Tie, 8.9" Long, 60lb Tensile Strength, PP, Black, 500/pkg
Global Part Name	T120S-PP-BK
Minimum Tensile Strength (Imperial)	60.0
Minimum Tensile Strength (Metric)	267.0
Length L (Imperial)	8.9
Length L (Metric)	225.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.30
Width W (Metric)	7.6
Bundle Diameter Min (Imperial)	0.50
Bundle Diameter Min (Metric)	12.7
Bundle Diameter Max (Imperial)	2.2
Bundle Diameter Max (Metric)	55.9
Thickness T (Imperial)	0.06

Thickness T (Metric) 1.6

Material Polypropylene (PP)

Material Shortcut PP

Flammability UL 94 HB

Halogen free Yes

Operating Temperature (Metric) -40°F to +239°F (-40°C to +115°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909987

Content Unit(BMEcat) pcs.

