



**NOTES:**

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. THREADED INSERTS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
3. COLLARS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
4. JACK SCREWS: STEEL; NICKEL PLATED
5. CONNECTOR IS PART MARKED: 165X16949X CONEC ABC

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		ISO 2768-m		 dim. in mm	scale: 2:1 (5:1)			
						material: SEE NOTES			
			date	name		title:			
			drawn	21.01.15	Henneboel		<b>SCREEN CAP</b> 50pos. for socket connector with jack screw		
			appd.	21.01.15	Lehmenkühler				
			norm						
		d-old			dwg no:		DIN-A3		
		a	Original			16K1A3574		sh: 1	
rev.	description	date	name			part no: 165X16949X			

RoHS compliant