



- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 - ▲ 4. RATING: 50VDC, 50mA
 5. OPERATING FORCE: 500±100 gms
 6. TRAVEL: 0.25mm +0.2/-0.1
 7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
 - ▲ 8. SILVER CONTACTS
 - ▲ 9. PACKAGE: 90 PCS PER TUBE
 10. ▲ DENOTES CRITICAL PARAMETER
 11. 2002/95/EC (ROHS) COMPLIANT
 12. LIFE: 100,00 CYCLES

E-SWITCH®

B	15934	ADDED LIFE NOTE	4/4/2006	BS
A	15887	RELEASED FOR PRODUCTION	3/23/06	PH
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE TL3301TF500QG				
SCALE	DATE	DR	DWG	REV
4:1	3/23/2006	PH	P010623	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED