

Type 1/2 surge protection plug - VAL-MS-T1/T2 48/12.5 ST - 2801242

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



L-N replacement plug for VAL-MS-T1/T2 48/12.5 plug-in lighting/surge arrester.

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	62.0 GRM
Custom tariff number	85366990
Country of origin	Germany

Technical data

Dimensions

Height	47 mm
Width	17.5 mm
Depth	67.3 mm
Horizontal pitch	1 Div.

Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Altitude	≤ 2000 m (NN)

General

Housing material	PBT / PA
Inflammability class according to UL 94	V0
Color	black
Standards for air and creepage distances	DIN EN 60664-1
	EN 61643-11
Mounting type	On base element
Type	Male

Type 1/2 surge protection plug - VAL-MS-T1/T2 48/12.5 ST - 2801242

Technical data

General

Number of positions	1
Surge protection fault message	Optical
Direction of action	L-N / L-PEN

Protective circuit

IEC test classification	I / II
	T1 / T2
EN type	T1 / T2
Nominal voltage U_N	60 V AC
	60 V DC
	- 48 V DC (RRH)
Maximum continuous operating voltage U_c	75 V AC
	100 V DC
U_T (TOV-proof)	100 V AC (5 s)
	130 V DC (5 s)
Nominal frequency f_N	50 Hz (60 Hz)
Residual current I_{PE}	≤ 0.6 mA
Standby power consumption P_c	≤ 90 mVA
Max. discharge current I_{max} (8/20) μ s	30 kA
Nominal discharge current I_n (8/20) μ s	12.5 kA
Impulse discharge current (10/350) μ s charge	6.25 As
Impulse discharge current (10/350) μ s, specific energy	39 kJ/ Ω
Impulse discharge current (10/350) μ s, peak value I_{imp}	12.5 kA
Voltage protection level U_p	≤ 0.4 kV
Voltage protection level U_p (L+) - (L-)	≤ 0.4 kV
Voltage protection level U_p (L+/L-) - PE	≤ 0.4 kV
Residual voltage	≤ 0.4 kV
	≤ 0.35 kV (at 10 kA)
	≤ 0.3 kV (at 5 kA)
	≤ 0.25 kV (at 3 kA)
Residual voltage (L+) - (L-)	≤ 0.4 kV
Residual voltage (L+/L-) - PE	≤ 0.4 kV
Response time	≤ 25 ns
Max. backup fuse with branch wiring	160 A (gL/gG)
Short-circuit resistance I_p with max. backup fuse (effective)	25 kA

Standards and Regulations

Standards/regulations	IEC 61643-11 2011
-----------------------	-------------------

Type 1/2 surge protection plug - VAL-MS-T1/T2 48/12.5 ST - 2801242

Technical data

Standards and Regulations

	EN 61643-11 2012
	UL 1449 ed. 3

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130802
eCl@ss 7.0	27130802
eCl@ss 8.0	27130802

ETIM

ETIM 2.0	EC000941
ETIM 3.0	EC000941
ETIM 4.0	EC000381
ETIM 5.0	EC000941

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / KEMA-KEUR / KEMA-KEUR / VDE Zeichengenehmigung / CCA / CCA / IECCEB Scheme / IECCEB Scheme / cULus Recognized

Ex Approvals

Type 1/2 surge protection plug - VAL-MS-T1/T2 48/12.5 ST - 2801242


Approvals


Approvals submitted


Approval details

UL Recognized 

cUL Recognized 


KEMA-KEUR 


KEMA-KEUR 

VDE Zeichengenehmigung 

CCA

CCA

IECEE CB Scheme 

IECEE CB Scheme 

Type 1/2 surge protection plug - VAL-MS-T1/T2 48/12.5 ST - 2801242

Approvals

