

| APPLICABLE STANDARD | | | | |
|---------------------|-----------------------------|--|---------------------------|-----------------|
| RATING | Operating Temperature Range | -40°C to 85°C (Note 1) | Storage Temperature Range | -10°C TO 60°C |
| | Voltage | 30V AC/DC | Applicable Connector | BM25-4S/2-V(**) |
| | Current Δ | Signal contact : 0.3A Power contact : 10.0A | | |

SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|------|-------------|--------------|----|----|
|------|-------------|--------------|----|----|

CONSTRUCTION

| | | | | |
|---------------------|---------------------------------------|-----------------------|---|---|
| General Examination | Visually and by measuring instrument. | According to drawing. | X | X |
| Marking | Confirmed visually. | According to drawing. | X | X |

ELECTRIC CHARACTERISTICS

| | | | | |
|-----------------------|------------------------------|--|---|---|
| Contact Resistance | 20mV AC or less 1kHz, 1m A . | Signal contact resistance: 30 mΩ MAX. Power contact resistance: 5 mΩ MAX. | X | - |
| Insulation Resistance | 100V DC. | 1000 MΩ MIN. | X | - |
| Voltage Proof | 150V AC for 1 min. | No flashover or breakdown. | X | - |

MECHANICAL CHARACTERISTICS

| | | | | |
|----------------------|--|---|---|---|
| Mechanical Operation | 10 times insertions and extractions. | ① Signal contact resistance: 30 mΩ MAX. Power contact resistance: 5 mΩ MAX. ② No damage, crack or looseness of parts. | X | - |
| Vibration | Frequency 10 to 55 to 10 Hz, approx. 5min, Single amplitude 0.75 mm, 10cycles, for 3 directions. | ① No electrical discontinuity of 1 μs. ② No damage, crack or Looseness of parts. | X | - |
| Shock | 490 m/s ² duration of pulse 11 ms at 3 times for 3 directions. | ① No electrical discontinuity of 1 μs. ② No damage, crack or looseness of parts. | X | - |

ENVIRONMENTAL CHARACTERISTICS

| | | | | |
|-----------------------------|---|---|---|---|
| Rapid Change of Temperature | Temperature -55 → +85°C Time 30 → 30 min Under 5 cycles. (Relocation time to chamber : within 2-3 min) | ① Signal contact resistance: 30 mΩ MAX. Power contact resistance: 5 mΩ MAX. ② Insulation resistance: 1000MΩ MIN. ③ No damage, crack or looseness of parts. | X | - |
| Damp Heat (Steady state) | Exposed at 40 ± 2 °C, 90 to 95 %, 96 h. | ① Signal contact resistance: 30 mΩ MAX. Power contact resistance: 5 mΩ MAX. ② Insulation resistance: 100MΩ MIN. ③ No damage, crack or looseness of parts. | X | - |
| Sulphur Dioxide | Exposed in 25 PPM for 96h, 25°C, 75%. (Refer to JIS C 60068) | Signal contact resistance: 30 mΩ MAX. Power contact resistance: 5 mΩ MAX. | X | - |

| COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|------------|--------------------------|------------|--------------|------------|
| Δ 1 | DIS-H-00001221 | TR. YUNOKI | TS. MIYAZAKI | 15. 12. 26 |

| | | | |
|---|----------|-------------|------------|
| REMARKS Note1: Include the temperature rising by current Unless otherwise specified, refer to JIS C 5402 and IEC 60512. | APPROVED | MO. ISHIDA | 15. 03. 26 |
| | CHECKED | YH. MICHIDA | 15. 03. 26 |
| | DESIGNED | TR. YUNOKI | 15. 03. 26 |
| | DRAWN | KR. AJITO | 15. 03. 26 |

| | | |
|--|-------------|------------------|
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | DRAWING NO. | ELC-358234-53-01 |
|--|-------------|------------------|

| | | | | |
|------------|---------------------------|----------|------------------|--------------|
| HRS | SPECIFICATION SHEET | PART NO. | BM25-4P/2-V (53) | |
| | HIROSE ELECTRIC CO., LTD. | CODE NO. | CL677-1201-2-53 | Δ 1/1 |