

MEDIUM VOLTAGE FUSES

Bussmann
Type (gR)

W/Out Striker	With Striker	Ampere
Part Number	Part Number	Rating
FWS-2A20F	FWS-2A20FI	2A
FWS-6A20F	FWS-6A20FI	6A
FWS-8A20F	FWS-8A20FI	8A
FWS-10A20F	FWS-10A20FI	10A
FWS-12A20F	FWS-12A20FI	12A
FWS-15A20F	FWS-15A20FI	15A

FWL-20A20F	FWL-20A20FI	20A
FWL-25A20F	FWL-25A20FI	25A
FWL-30A20F	FWL-30A20FI	30A

Ratings: 1200VAC (SWE-FWL 20-30A)
1400VAC (SWE-FWS 8-15A)
2100VAC (SWE-FWS 2-6A)
1000VDC (SWE-FWL / FWS 2-30A)

I.R.: 45kA RMS Sym.
30kA@1000VDC

Pack Size (box): 10


Price & Availability: Please contact sales

Holders: Clips (p111)
Base and Disconnect (As below)


Features and Benefits

- Excellent cycling capability and dc performance
- Low arc voltage and low energy let-through (I₂t)
- Low watts loss in a compact size
- Used with finger-safe holders/blocks

Dimensions - mm (Inches)



Indicating Version - Dimensions - mm (Inches)



Dimensions in MM



HIGH VOLTAGE

Typical Applications

- DC common bus
- DC drives
- Power converters/rectifiers
- Reduced voltage starters
- Traction aux circuits
- Capacitor protection

FUSE DISCONNECT

Isolator Style

Part Number	Nbr of Poles
SWE-CH127-1	1

Rating: 63A

Voltage: 1500VAC / 1500VDC

Body: Black

Pack Size: 1, 4

Terminals: Screw

Features: Cover extracts fuse upon opening. Interlockable.

Dimensions: Depth: 102mm (closed) / 185mm (open).

Length: 200mm

Single Pole Width : 39mm

Two Pole Width : 78mm

Three Pole Width : 117mm

Suit Fuse: 20 x 127mm (Medium Voltage Fuses)

Notes: Do not open under load. Contact sales for further information.

Approvals: IEC RoHS

