

Radial Leaded Inductors[LHL]

LHL08TB331K



■ Features

- Item Summary
330uH±10%, 0.44A, φ9.0x9.5mm Radial
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping 1000pcs

■ Products characteristics table

| | |
|---|---|
| Inductance | 330 uH ± 10 % |
| Case Size (mm) | 9.0x9.5 |
| Rated Current (max) | 0.44 A |
| DC Resistance (max) | 0.97 Ω |
| Q (min) | 25 |
| LQ Measuring Frequency | 0.796 MHz |
| Self Resonant Frequency (min) | 3.2 MHz |
| Operating Temp. Range | -25 to +105 °C (Including-self-generated heat) |
| Temperature characteristic (Inductance change) | ± 7 % |
| RoHS2 Compliance (10 subst.) | Yes |
| REACH Compliance (173 subst.) | Yes |
| Soldering | Wave |

■ External Dimensions

| | |
|--------------|---------------|
| Dimension D | Max φ9.0 mm |
| Dimension H2 | Max 9.5 mm |
| Dimension d | φ0.6 ±0.05 mm |
| Dimension F | 5.0 ±1.0 mm |
| Dimension l | 5.0 ±1.0 mm |

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.