



Male connectors, straight

Identification	No. of contacts	Part number	Dimensions in mm						
			A	B	C	D	E	F	G
Male connector, straight, stacking heights 1.75 / 3.25 mm	6	15 1 . 006 . 601 ...	2.54	6.96	8.89	5.76	4.76	6.56	1.05
	8	15 1 . 008 . 601 ...	3.81	8.23	10.16	7.03	6.03	7.83	1.69
	10	15 1 . 010 . 601 ...	5.08	9.50	11.43	8.30	7.30	9.10	2.32
	12	15 1 . 012 . 601 ...	6.35	10.77	12.70	9.57	8.57	10.37	2.96
	14	15 1 . 014 . 601 ...	7.62	12.04	13.97	10.84	9.84	11.64	3.59
	16	15 1 . 016 . 601 ...	8.89	13.31	15.24	12.11	11.11	12.91	4.23
	18	15 1 . 018 . 601 ...	10.16	14.58	16.51	13.38	12.38	14.18	4.88
	20	15 1 . 020 . 601 ...	11.43	15.85	17.78	14.65	13.65	15.45	5.50
	22	15 1 . 022 . 601 ...	12.70	17.12	19.05	15.92	14.92	16.72	6.13
	24	15 1 . 024 . 601 ...	13.97	18.39	20.32	17.19	16.19	17.99	6.77
	26	15 1 . 026 . 601 ...	15.24	19.66	21.59	18.46	17.46	19.26	7.40
	28	15 1 . 028 . 601 ...	16.51	20.93	22.86	19.73	18.73	20.53	8.04
	30	15 1 . 030 . 601 ...	17.78	22.20	24.13	21.00	20.00	21.80	8.67
	32	15 1 . 032 . 601 ...	19.05	23.47	25.40	22.27	21.27	23.07	9.31
	34	15 1 . 034 . 601 ...	20.32	24.74	26.67	23.54	22.54	24.34	9.94
	36	15 1 . 036 . 601 ...	21.59	26.01	27.94	24.81	23.81	25.61	10.58
	38	15 1 . 038 . 601 ...	22.86	27.28	29.21	26.08	25.08	26.88	11.21
	40	15 1 . 040 . 601 ...	24.13	28.55	30.48	27.35	26.35	28.15	11.85
	42	15 1 . 042 . 601 ...	25.40	29.82	31.75	28.62	27.62	29.42	12.48
	44	15 1 . 044 . 601 ...	26.67	31.09	33.02	29.89	28.89	30.69	13.12
	46	15 1 . 046 . 601 ...	27.94	32.36	34.29	31.16	30.16	31.96	13.75
	48	15 1 . 048 . 601 ...	29.21	33.63	35.56	32.43	31.43	33.23	14.39
	50	15 1 . 050 . 601 ...	30.48	34.90	36.83	33.70	32.70	34.50	15.02
	52	15 1 . 052 . 601 ...	31.75	36.17	38.10	34.97	33.97	35.77	15.66
	54	15 1 . 054 . 601 ...	33.02	37.44	39.37	36.24	35.24	37.04	16.29
	56	15 1 . 056 . 601 ...	34.29	38.71	40.64	37.51	36.51	38.31	16.93
	58	15 1 . 058 . 601 ...	35.56	39.98	41.91	38.78	37.78	39.58	17.56
	60	15 1 . 060 . 601 ...	36.83	41.25	43.18	40.05	39.05	40.85	18.20
	62	15 1 . 062 . 601 ...	38.10	42.52	44.45	41.32	40.32	42.12	18.83
	64	15 1 . 064 . 601 ...	39.37	43.79	45.72	42.59	41.59	43.39	19.47
	66	15 1 . 066 . 601 ...	40.64	45.06	46.99	43.86	42.86	44.66	20.10
	68	15 1 . 068 . 601 ...	41.91	46.33	48.26	45.13	44.13	45.93	20.74
	70	15 1 . 070 . 601 ...	43.18	47.60	49.53	46.40	45.40	47.20	21.37
	72	15 1 . 072 . 601 ...	44.45	48.87	50.80	47.67	46.67	48.47	22.01
	74	15 1 . 074 . 601 ...	45.72	50.14	52.07	48.94	47.94	49.74	22.64
	76	15 1 . 076 . 601 ...	46.99	51.41	53.34	50.21	49.21	51.01	23.28
	78	15 1 . 078 . 601 ...	48.26	52.68	54.61	51.48	50.48	52.28	23.91
	80	15 1 . 080 . 601 ...	49.53	53.95	55.88	52.75	51.75	53.55	24.55
	82	15 1 . 082 . 601 ...	50.80	55.22	57.15	54.02	53.02	54.82	25.18
	84	15 1 . 084 . 601 ...	52.07	56.49	58.42	55.29	54.29	56.09	25.82
	86	15 1 . 086 . 601 ...	53.34	57.76	59.69	56.56	55.56	57.36	26.45
	88	15 1 . 088 . 601 ...	54.61	59.03	60.96	57.83	56.83	58.63	27.09
	90	15 1 . 090 . 601 ...	55.88	60.30	62.23	59.10	58.10	59.90	27.72
	92	15 1 . 092 . 601 ...	57.15	61.57	63.50	60.37	59.37	61.17	28.36
	94	15 1 . 094 . 601 ...	58.42	62.84	64.77	61.64	60.64	62.44	28.99
	96	15 1 . 096 . 601 ...	59.69	64.11	66.04	62.91	61.91	63.71	29.63
	98	15 1 . 098 . 601 ...	60.96	65.38	67.31	64.18	63.18	64.98	30.26
	100	15 1 . 100 . 601 ...	62.23	66.65	68.58	65.45	64.45	66.25	30.90

Please insert digit for stacking height

1.75 mm ▶ 1
3.25 mm ▶ 2

for performance level 1
for performance level S4
for performance level 2

2
5
6

333
000

for samples
for 280 pieces on reel