



LF version	Contact area (1 face)	Terminal area (2 faces)
LFS	0.5 um min Ag plate over 1.3 um min Nickel plate	0.2-0.6 um Ag plate all over 1.3 um Ni plate all over

Reference	Designation	Plating	Switching Force (N)
YT1053530FP LFS	KT11P3JM34LFS	SILVER	1.725 TO 2.875

TOLERANCE:
 LINEAR: ± 0.12
 ANGLUAR: ± 3°

FOR REFERENCE ONLY
 仅供参考
 THIS PRINT WILL NOT BE UPDATED
 不作自动更新

DO NOT SCALE		PDM:		A3/B
Drawn	CDY 03-Apr-06	Material:	ITT Industries Cannon Electronics (SZ) Co. Ltd. Toupandun Industrial Area, Jinda Cheng, Xiner Village, Shajing Town, Baoan District, Shenzhen City PRC 518125	
Checked	KT 03-Apr-06	 Surface Roughness		
Engineer.	CDY 03-Apr-06			
Manufact.	.	Treatment:		
Assembly	.	Quality	Ref:	Pro/E Generic Model Title KT11P3JMLFx
Approvals	Sign Date	Dimensions in: mm	Cust Spec No:	
- RIE-1707 INITIAL ISSUE 03-Apr-06		Scale 10:1 Sheet 1 of 1		
Iss Rev DCN/ECN or Description Date		This is issued in strict confidence on condition that it is not used as a basis for manufacture or sale and that it is not copied reprinted or disclosed to a third party either wholly or in part without the prior written consent of ITT Industries © 31-Mar-06		