



PANEL THICKNESS	X dimension
0.75-1.25 [0.030-0.049]	19.2-0.1 [0.756]
1.25-2.0 [0.049-0.079]	19.4-0.1 [0.764]
2.0-3.0 [0.079-0.118]	19.8-0.1 [0.780]



PANEL CUTOUT
NOT TO SCALE

SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
DN	OFF	(DN)
1-1b	OPEN	1-1a



CIRCUIT: SPDT

(<)=Momentary

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
 3. TERMINAL NOS. FOR REF ONLY.
 4. RATING: 15A @ 125VAC OR 6A @ 250VAC
 5. MATERIALS: TERMINALS: Silver Plated Copper Alloy
CONTACTS: Coin Silver, Silver Plated
 6. ELECTRIC LIFE: 10,000 cycles
 7. CONTACT RESISTANCE: <20 Mega Ω
 8. INSULATION RESISTANCE: >1000 Mega Ω
 9. DIELECTRIC STRENGTH: >1500 V 1 minute
>3000 V between poles
 10. 2002/95/EC (ROHS) COMPLIANT



R1966HBLKBLKEF

REV.	ECN No.	DESCRIPTION	DATE	CHKD	TN
B	16801	UPDATED NOTES, FIXED TERM	12/28/06		
A	11463	RELEASED FOR PRODUCTION	5/24/01		CJB

TITLE	SCALE	DATE	DR	DWG	REV
R1966HBLKBLKEF	1.5:1	12/28/06	TN	M301224	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED