

Product Guide

Transceivers, Transponders,
and Active Optical Cables



FINISAR®



Transceivers, Transponders, and Active Optical Cables

SFP (copper and optical; longwave, shortwave and WDM)

DATACOM applications using Fast Ethernet, Gigabit Ethernet, 1x/2x/4x Fibre Channel

TELECOM applications using OC-3/STM-1, OC-12/STM-4, OC-48/STM-16, EPON/GPON and Wireless/CPRI across all reaches

Features

- 3.3 V operating voltage
- Distances from very short links up to 100+ km
- Wide operating temperature range
- Metal enclosure for lower EMI
- Digital diagnostics
- Wireless CPRI compliant



SFP+/SFP28

(optical; longwave, shortwave, DWDM and tunable)

DATACOM applications using 10G and 25G Ethernet and 2x/4x/8x/10x/16x/32x Fibre Channel (LW and SW)

TELECOM applications using either OC-192/STM-64, 10G Ethernet, or Wireless/CPRI

Features

- 3.3 V operating voltage
- Supports bit rates up to 28.05 Gb/s (LW, SW, and DWDM) and 11.3 Gb/s (Tunable)
- Distances from short links up to 80 km metro (LW, SW, and DWDM) and 80km (Tunable)
- Wide operating temperature range
- Digital diagnostics
- Wireless CPRI compliant (LW and SW)
- Bi-directional SFP+ transceiver available



CFP/CFP2/CFP4/CFP8

(optical; longwave and shortwave)

DATACOM applications using 100G and 400G Ethernet

TELECOM applications using OTU4

Features

- Hot-pluggable, MSA-compliant CFP, CFP2, CFP4 and CFP8 form factors
- Supports 103.1 Gb/s to 425 Gb/s aggregate bit rates
- Maximum link length of 100m on OM3 MMF, 150m on OM4 MMF, 10km on SMF
- 3.3 V operating voltage



QSFP+/QSFP28 (optical; longwave and shortwave)

DATACOM applications using 40G and 100G Ethernet and high-density 10G and 25G Ethernet

TELECOM applications using OTU3 and OTU4

Features

- Four-channel full-duplex transceiver module
- Hot-pluggable, MSA-compliant QSFP+ and QSFP28 form factors
- Maximum link length of 300m on OM3 MMF, 400m on OM4 MMF, and 40 km on SMF
- 3.3 V operating voltage
- Digital diagnostics
- Wireless CPRI compliant (LW and SW)



CXP (optical; shortwave)

DATACOM applications using 100G Ethernet and chassis interconnections

Features

- Twelve-channel full-duplex transceiver module
- Hot Pluggable CXP form factor
- Maximum link length of 300m on OM3 MMF and 400m on OM4 MMF
- Multirate capability: supports 1.06 Gb/s to 12.5 Gb/s per channel



Active Optical Cables

SFP^{wire}


SFP+ Active Optical Cable for 10G and 25G Ethernet. Also available with Connectivity Diagnostics.[®]

quad^{wire}

40 Gb/s to 100 Gb/s Parallel Active Optical Cable for 40GbE and 100GbE, InfiniBand 4xQDR, InfiniBand 4xFDR, InfiniBand 4xEDR and Intel[®] Omni-Path Architecture. Also available with Connectivity Diagnostics.[®]

C.wire

150 Gb/s Parallel Active Optical Cable for 100GbE and InfiniBand 12xQDR.



Optical Engines (optical; shortwave)

DATACOM applications for inter-chassis connections

Features

- Twelve-channel full-duplex transceiver modules
- Maximum link length
100m at 10 Gb/s on OM3 MMF
70m at 25 Gb/s on OM4 MMF
- Multirate capability: supports 1 Gb/s up to 28.1 Gb/s per channel



X2 (optical; longwave and shortwave)

DATACOM applications using 10G Ethernet

Features

- Supports bit rates up to 10.5 Gb/s
- Distances up to 10 km
- Digital diagnostics



Coherent (optical; longwave)

TELECOM 100 Gb/s and 200 Gb/s applications

Features

- Pluggable CFP2-ACO analog coherent optics module
 - Highest density coherent interface
 - Enables “pay-as-you-grow” deployment of coherent optics
 - Analog interface is compatible with any external DSP
 - Modulation format independent, supports data rates > 200 Gb/s



Endurance Compact Transceivers (optical; longwave and shortwave)

Features

- Compact form-factor for high-density solutions
- Data rate flexibility including 1G and 10G Ethernet, Fast Ethernet, and 1x/2x/4x/8x/16x Fibre Channel
- Board-mounted for an edge optical interface or internal mounting
- Designed for rugged applications



XFP (optical; longwave, shortwave, DWDM, and tunable)

DATACOM applications using 10G Ethernet and 10x Fibre Channel

TELECOM applications using OC-192/STM-64

Features

- Supports bit rates up to 11.3 Gb/s
- Distances up to 200 km (LW, SW, and DWDM) and 80 km (Tunable)
- Digital diagnostics
- Wide operating temperature range versions available



SFF (optical; longwave and shortwave)

DATACOM applications using Gigabit Ethernet, 1x/2x/4x Fibre Channel

TELECOM applications using OC-3/STM-1, OC-12/STM-4 and OC-48/STM-16 across all reaches

Features

- Distances from very short links up to 80 km
- Wide operating temperature range
- Available in 2x5, 2x7 or 2x10. 2x7 and 2x10 incorporate digital diagnostics



Finisar’s Digital Diagnostics

Finisar’s transceivers feature a microprocessor and diagnostics interface that provide performance information on the data link. Users can remotely monitor—in real-time—received optical power, transmitted optical power, laser bias current, transceiver input voltage and transceiver temperature of any transceiver in the network. These patented digital diagnostic functions provide network managers with a highly accurate, cost-effective tool for implementing reliable performance monitoring.

Finisar’s Connectivity Diagnostics

Several of Finisar’s products feature the Connectivity Diagnostics® suite of tools, which helps data center technicians quickly and intuitively find specific modules in a sea of sockets using a visual indicator. LynkFind™ allows an operator to light up the pull-tab of the module at the far-end of a link by pressing the pull-tab of the near-end module. LynkGuardian™ lights up the modules at both ends of a link when either module experiences a fault. LynkCommander™ allows a network operations center to light up a module for easy identification on the data center floor. Together, these patented tools bring the intelligence normally available through data center monitoring software to a simple and intuitive visual indicator. The benefits to the data center operator enable faster installation and maintenance, easier troubleshooting, and simplified operations.

Technology Innovator.
Broad Product Portfolio.
Trusted Partner.



FINISAR[®]

1389 Moffett Park Drive
Sunnyvale, CA 94089-1133
Telephone: +1 408-548-1000

Email: sales@finisar.com
Blog: www.finisar.com/blogs/lightspeed
www.finisar.com

© 2018 Finisar Corporation. All rights reserved. Finisar, SFPwire, Quadwire, Cwire, and Connectivity Diagnostics are registered trademarks and LynkFind, LynkGuardian, and LynkCommander are pending trademarks of Finisar Corporation. All other marks are property of their respective owners. Features and specifications are subject to change without notice. 02/18



Visit Our Website

