

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION DATE: - 2011
 © COPYRIGHT 2011 ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
H	-	P	LTR	DESCRIPTION	DATE	DWN	APVD
		F		EH01-0232-04	16 FEB 04	-	PDJ
		G		ECR-06-014824	19 JUN 06	-	JvdH
		G1		ECR-10-026542	25MAY2011	KK	HMR
		G2		PART NUMBER REACTIVATION	8-8-11	SP	RP

Top view dimensions: "A" = (N-1) x 1.27, "B", "C", 1.68, 0.50, 2.54, 5.15 MAX., 7.0, "E", 1.27.

Side view dimensions: 0.10 ALL CONTACTS, 0.50.

Detail view dimensions: 7.0, 0.30, 4.6^{+0.2}/_{-0.1}, 6.5±0.2.

SECTION A-A

PACKAGING/REELING DIRECTION

USER DIRECTION OF FEED

Dimensions: D = mm, 44 mm, 24 mm.

NOTES:

- PACKAGING ACCORDING EIA-481/DIN IEC 286. REELDIA 380 MM
- TIN OVER NICKEL PLATING.

NUMBER OF POSITIONS N	PN -WITHOUT	PN -WITH	"A"	"B"	"C"	TAPE WIDTH "D"	"E"
20	2-338728-0	9-338728-0	24.1	28.6	27.5	44	10.2
18	1-338728-8	8-338728-8	21.6	26.1	24.9	44	8.9
16	1-338728-6	8-338728-6	19.0	23.5	22.4	44	7.7
14	1-338728-4	8-338728-4	16.5	21.0	19.9	44	6.4
12	1-338728-2	8-338728-2	14.0	18.5	17.3	44	5.1
10	1-338728-0	8-338728-0	11.4	15.9	14.8	24	3.9
8	338728-8	7-338728-8	8.9	13.4	12.2	24	2.6
6	338728-6	7-338728-6	6.4	10.8	9.7	24	1.3
4	338728-4	7-338728-4	3.8	8.3	7.2	24	0.1

RECOMMENDED PCB LAY-OUT TOP VIEW

Dimensions: 1.50, 3.00 (MINIMUM SOLDER-PATH LENGTH), 1.50, 7.50, 1.27, 2.54, "A"

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	M. Gosselink	PA 4.6, 30% GF, COLOR GREY
CHK	-	PHOSPHOR BRONZE
APVD	-	Pa 4.6, 30% GF, COLOR: RED
PRODUCT SPEC	108-19052	Material
APPLICATION SPEC	-	Finish

Micro-MaTch Male On Board SMD connector

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	©-338728	-

CUSTOMER DRAWING SCALE 5:1 SHEET 1 OF 1 REV G2

1470-19 (3/11)

Pro/ENGINEER DRAWING