




MXC6232xEP-B Prototyping Board

MXC6232xEP-B

GENERAL DESCRIPTION

The MXC6232xEP-B provides a convenient and easy way to evaluate and prototype with the MXC6232xEP dual axes accelerometer. The accelerometer and passive components are SMT mounted on the board. Each pin of the MXC6232xEP SMT device is brought out to standard 0.10 inch on center connections on the sides of the prototyping board. Wires can either be soldered directly to the prototyping board or the DIP pins can be used with widely available breadboard kits.

For complete performance specifications of the MXC6232xEP refer to the MXC6232xEP datasheet.




MXC6232xEP-B

PIN DESCRIPTION


Pin	Name	Description
P1-1	VDD	Supply Voltage 2.7 to 3.6 V
P1-2	NC	No Connect
P1-3	NC	No Connect
P1-4	GND	Ground
P2-1	NC	No Connect
P2-2	SDA	Serial Data Line for I2C Bus
P2-3	SCL	Serial Clock Line for I2C Bus
P2-4	NC	No Connect

SCHEMATIC OF THE MXC6232xEP-B



MXC6232xEP-B

PCB CONNECTION DIMENSIONS



MXC6232xEP-B

Information furnished by MEMSIC is believed to be accurate and reliable. However, no responsibility is assumed by MEMSIC for its use, nor for any infringements of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MEMSIC.

©MEMSIC, Inc.
 One Technology Drive, Suite 325, Andover, MA, 01810, USA
 Tel: +1 978 738 0900 Fax: +1 978 738 0196
 www.memsic.com