



LOC	DIST	ZONE	LTR	REVISIONS	DATE	APPD
G	14	B		REVISED PER 0720-0230-93	2/25/94	DAL

METRIE
DIMENSIONS LISTED IN mm [INCHES]

AMP WIRE RANGE 16-14 AWG STRANDED	IL E13288 Listed 16-14 AWG STRANDED
---	--

AMP LR7189 Certified NOT CERTIFIED	MILITARY P/N AND CLASS NOT APPLICABLE
---	---

△ STAMP AMP 16-14* APPROX AS SHOWN

AMP INCORPORATED
CUSTOMER SERVICE SYSTEMS

FOR ADDITIONAL
PRODUCT INFORMATION OR
COPIES OF DRAWINGS
AND TECHNICAL DOCUMENTS
1-800-522-6752
PRODUCT INFORMATION CENTER

FOR APPLICATION
TOOLING INFORMATION
1-800-722-1111
TOOLING ASSISTANCE CENTER

FOR ORDER ENTRY
1-800-526-5142

MAX RECOMMENDED OPERATING
TEMPERATURE: 170°C MAX

VOLTAGE RATING:
NOT APPLICABLE

WIRE CROSS SECTIONAL AREA RANGE:
1.04-2.62mm² [2,050-5,180] CIR MILS
STRANDED

DO NOT SCALE PRINT.
UNLESS SPECIFIED
DIMENSIONS IN - FINISHES -
TOLERANCES ON:
2 PLC DEC ±
3 PLC DEC ±
ANGLES ±
MATERIAL:
COPPER PER
ASTM B-152
ANNEALED

FINISH:
TIN PLATE
0.00254L [0.00100] MIN
THK PER MIL-T-10727

DR 2-17-93
TA BRINKMAN

CHK 2-17-93
DA PATTERSON

APPD 2-17-93
DE MILLER

APPD 2-17-93
JL HECKLEY

PRODUCT SPEC

AMP
AMP Incorporated
Harrisburg, PA 17105-3508

TERMINAL, SPADE TONGUE,
BUDGET

APPLICATION SPEC

SIZE CAGE CODE DRAWING NO
G 00779 G-31704

SCALE 10:1

WEIGHT

SHEET 1 OF 1

31704
PART NO

31704