


MATERIAL
 INSULATOR: PBT.
 CONTACT: COPPER ALLOY.
 PLATING: MATING AREA - GOLD FLASH OVER NICKEL.
 SOLDER AREA - TIN/LEAD OVER NICKEL.

ELECTRICAL
 VOLTAGE RATING: 250 VAC RMS.
 CURRENT RATING: 1 AMP.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC RMS 60HZ FOR 1 MINUTE.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN AT 500 VDC.
 CONTACT RESISTANCE: 30 MILLIOHMS MAX AT 1 AMP DC.

MECHANICAL
 RETENTION FORCE: 460 GRAMS MIN PER CONTACT.
 INSERTION FORCE: 230 GRAMS MAX PER CONTACT PAIR.
 WITHDRAWAL FORCE: 15 GRAMS MIN PER CONTACT PAIR.

ENVIRONMENTAL
 TEMPERATURE RANGE: -55°C TO +85°C.



Sullins Electronics
 San Marcos, CA
 www.sullinselectronics.com

TITLE: PCI CARD EDGE SLOT, STR. MOUNT

PART NO. TRWB060DKRQ-1578

DWG NO. P120-05-901

TOLERANCE		ANGLES	
LINEAR	X ± 0.20	X ±	X ±
	X ± 0.15	X ±	X ±
	XX ± 0.10	XX ±	XX ±
REV	ECN NO.	NAME	DATE
			XXX ± 0.05
			XXX ±

APPD:	MAT'L:	FINISH:
CHKD:	QTY:	
DRWN: Jason Deng		

UNITS	SCALE	SHEET	REV
MM	1 : 1	1 OF 1	B