



PIN OUT

| | | | |
|----|----|-----------|--------|
| P1 | P2 | P1 | P2 |
| 1 | 1 | 10 | ORANGE |
| 6 | 6 | 11 | WHITE |
| 2 | 2 | 12 | YELLOW |
| 7 | 7 | 13 | GREEN |
| 3 | 3 | 14 | RED |
| 8 | 8 | SHELL | BRAID |
| 4 | 4 | CENTER | |
| 5 | 5 | SHIELDING | |

Material:

- 1.CABLE:28AWG(7/0.127 T.C)*3COAX(75 OHMS)+INSULATION:FO-PE INNER JACKET:PVC OD:Ø2.5± 0.1mm(UL-1354)+28AWG(7/0.127 T.C)*7C+ INSULATION:SR-PVC ID:Ø0.85± 0.05mm(UL-1061)+AL/MY+DRAIN WIRE:26AWG(7/0.16 T.C)+BRAID SHIELD(85%)+OUTER JACKET:PVC COLOR:BEIGE,OD:Ø8.5± 0.15mm UL-2919
- 2.CONNECTOR:
P1:HDB 15P MALE,GOLD FLASH CONTACT, NICKEL PLATED SHELL (THE 9TH PIN UNLOAD)
P2:HDB 15P FEMALE,GOLD FLASH CONTACT, NICKEL PLATED SHELL
- 3.FERRITE CORE:17.5*28.5*9.5mm
- 4.SHIELD:COPPER-FOIL 360° SOLDERED TO CONNECTOR SHELL & CABLE BRAID
- 5.HOOD:MOLDED TYPE,PVC 45P,COLOR:BEIGE.
- 6.ELECTRONIC TEST: <1>.100% OPEN SHORT & MIS WIRE TEST <2>.CONTACT RESISTANCE 3 OHMS MAX <3>.INSULATION RESISTANCE 20M OHMS MIN
- 7.PACKING:SEE P-0039 REV.C PACKING DRAWING (HANKING SIZE MUST BE SMALLER THAN PACKING) PACKING TYPF· DB VP4



| | | | | | | | |
|-----------|-------|--|--|--|----------|----------|----------|
| Scale | 1:1 | | | | | | Name |
| TOLERANCE | | | | | | | Chappell |
| X.X | ±0.40 | | | | Drawn | 11.16.11 | |
| X.XX | ±0.25 | | | | Approved | | |
| X.XXX | ±0.15 | | | | | | |
| Angle | ±3° | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |



| | |
|-------------|---|
| Item No. | AK3915XF |
| Title | Premium XGA Monitor Extension Cable - 15 Meters w/Ferrite core, HD D-Sub 15 pin Male <=> Female |
| Drawing No. | |
| Replace | rev00 |
| Sheet | |