3M

All 3M Products Innovation About 3M

⌂Industrial Adhesives & Tapes

Products | Applications | Industries | Capabilities | Support   Where to Buy

3M™ Dual Lock™ Reclosable Fastener SJ3550 250 Black, 2 in x 50 yd 0.22 in (5.6 mm), 1 per case Bulk

3M ID 70070521110   UPC# 00021200658174   Part Number SJ3550   3M Product Number SJ3550

3M™ Dual Lock™ Reclosable Fastener SJ3550 is a general purpose acrylic adhesive on the back of a black, polypropylene reclosable fastner. 3M™ Dual Lock™ Reclosable Fastener SJ3550 has 250 stems per square inch with an 0.23 inch engaged thickness. Offers a closure life of 1,000.

- A black fastener with mushroom shaped stems backed with a white, general purpose acrylic pressure sensitive adhesive.
- Type 250 stem density polyolefin fastener which mates to Type 170, 250 or 400.
- Designed to bond to metals, glass and medium to high surface energy plastics and paint.
- General Industrial, Speciality Vehicles, Transportation, Military, Packaging, Medical, Point of Purchase Displays, Exhibits, Electronics, Construction, Furniture, Maintenance Repair and Operations (MRO).
- Attach Doors, Access Panels, Signs, Cushions, Headliners and Display Components.

View All Images

Where to Buy

Like Sign Up to see what your friends like.

- Print
- Share

Need Help?

Questions? We can help
Contact Us

Overview | **Documents**

3M™ Dual Lock™ Reclosable Fastener SJ3550 has a high temperature performance of up 200 degrees fahrenheit and can be used indoors and outdoors. 3M™ Dual Lock™ Reclosable Fastener SJ3550 is for use with metals (aluminum, stainless steel), glass and high surface energy plastics (acrylic, polycarbonate, ABS) and can be opened and closed 1,000 times.

Specifications

Adhesive Type	General Purpose Acrylic Adhesive
Applications	Wall Panel Attachment, Wall Headliner Attachment, Attaching City Bus light fixtures, Privacy Curtain Rail Attaching, Ceiling Attachment, Sunroof Trim Attachment
Brand	Dual Lock
Closure Life	1000
Color	Black
Engaged Thickness	0.23 Inch
Flame Retardant	No
Indoor/Outdoor	Both
Industries	Transportation, Specialty Vehicle, Construction, Automotive, Furniture, Medical, Military & Government, General Industrial, Retail, MRO, Electronics, Packaging
Length	50 Linear Yard

Length (Metric)	45.72 m
Liner Thickness	4 mil
Liner Type	Clear Polyolefin
Low Profile	No
Maximum Operating Temperature (Celsius)	93 Degree Celsius
Maximum Operating Temperature (Fahrenheit)	200 Degree Fahrenheit
Product Form	Roll
Stem Density	250
Width	2 Inch
Width (Metric)	50.8 mm

3M: News | Careers | Partners & Suppliers | Investor Relations | MSDS Search | Transport Information Search | Contact 3M

Legal Information | Privacy Policy