


## FK-MC 0,5/ 4-ST-2,5

Order No.: 1881341

The figure shows a 10-position version of the product

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1881341>

Plug component, Nominal current: 4 A, Nom. voltage: 100 V, Pitch:  
2.5 mm, Number of positions: 4, Connection type: Spring-cage conn.,  
Color: green

| Commercial data          |                    |
|--------------------------|--------------------|
| EAN                      | 4017918156596      |
| Pack                     | 50 pcs.            |
| Customs tariff           | 85366990           |
| Weight/Piece             | 0.002772 KG        |
| Catalog page information | Page 136 (CC-2009) |

**Product notes**WEEE/RoHS-compliant since:  
01/01/2003

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

| Technical data                |        |
|-------------------------------|--------|
| <b>Dimensions / positions</b> |        |
| Pitch                         | 2.5 mm |
| Dimension a                   | 7.5 mm |
| Number of positions           | 4      |

**Technical data**

|                                    |                                                        |
|------------------------------------|--------------------------------------------------------|
| Insulating material group          | I                                                      |
| Rated surge voltage (III/3)        | 1.5 kV                                                 |
| Rated surge voltage (III/2)        | 2.5 kV                                                 |
| Rated surge voltage (II/2)         | 2.5 kV                                                 |
| Rated voltage (III/2)              | 160 V                                                  |
| Rated voltage (II/2)               | 320 V                                                  |
| Connection in acc. with standard   | EN-VDE                                                 |
| Nominal current $I_N$              | 4 A                                                    |
| Nominal voltage $U_N$              | 100 V                                                  |
| Nominal cross section              | 0.5 mm <sup>2</sup>                                    |
| Maximum load current               | 4 A (with 0.5 mm <sup>2</sup> conductor cross section) |
| Insulating material                | PA                                                     |
| Inflammability class acc. to UL 94 | V0                                                     |
| Stripping length                   | 8 mm                                                   |

**Connection data**

|                                                                            |                      |
|----------------------------------------------------------------------------|----------------------|
| Conductor cross section solid min.                                         | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.                                         | 0.5 mm <sup>2</sup>  |
| Conductor cross section stranded min.                                      | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded max.                                      | 0.5 mm <sup>2</sup>  |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.25 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 0.5 mm <sup>2</sup>  |
| Conductor cross section AWG/kcmil min.                                     | 26                   |
| Conductor cross section AWG/kcmil max                                      | 20                   |

**Certificates / Approvals**



Certification

CB, CUL, GOST, UL, VDE-PZI

**CUL**

|                       |       |
|-----------------------|-------|
| Nominal voltage $U_N$ | 125 V |
| Nominal current $I_N$ | 4 A   |

|                       |       |
|-----------------------|-------|
| AWG/kcmil             | 28-20 |
| <b>UL</b>             |       |
| Nominal voltage $U_N$ | 125 V |
| Nominal current $I_N$ | 4 A   |
| AWG/kcmil             | 28-20 |

**Accessories**



| Item           | Designation              | Description                                                                                                                                                              |
|----------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Marking</b> |                          |                                                                                                                                                                          |
| 0804853        | SK 2,54/2,8:FORTL.ZAHLEN | Marker card, printed horizontally, self-adhesive, 10-section marker strip, 14 identical decades marked 1-10, 11-20 etc. up to 91-100, sufficient for 140 terminal blocks |
| <b>Tools</b>   |                          |                                                                                                                                                                          |
| 1205202        | SZS 0,4X2,0              | Screwdriver, bladed, matches all screw terminal blocks up to 1.5 mm <sup>2</sup> connection cross section, blade width: 2.5 mm, without approvals                        |

**Additional products**


| Item           | Designation        | Description                                                                                                                |
|----------------|--------------------|----------------------------------------------------------------------------------------------------------------------------|
| <b>General</b> |                    |                                                                                                                            |
| 1881464        | MC 0,5/ 4-G-2,5    | Header, Nominal current: 4 A, Nom. voltage: 80 V, Pitch: 2.5 mm, Number of positions: 4, Color: green, Assembly: Soldering |
| 1894820        | MCD 0,5/ 4-G1-2,5  | Header, Nominal current: 4 A, Nom. voltage: 80 V, Pitch: 2.5 mm, Number of positions: 4, Color: green, Assembly: Soldering |
| 1894930        | MCDV 0,5/ 4-G1-2,5 | Header, Nominal current: 4 A, Nom. voltage: 80 V, Pitch: 2.5 mm, Number of positions: 4, Color: green, Assembly: Soldering |
| 1881574        | MCV 0,5/ 4-G-2,5   | Header, Nominal current: 4 A, Nom. voltage: 80 V, Pitch: 2.5 mm, Number of positions: 4, Color: green, Assembly: Soldering |

**Diagrams/Drawings**

Diagram



Dimensioned drawing



**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;