

## Corrugated tube screw connection - HC-B-GCA-M32-PLRBK - 1412022

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



EVO corrugated pipe screw connection, size: M32, protection class: IP66, plastic



### Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	80.0 g
Custom tariff number	39269097
Country of origin	Poland

### Technical data

#### General

Assembly instructions	Please observe the installation note provided for the WP-PA HF-HB....BK corrugated pipe
-----------------------	---

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 115 °C
Degree of protection	IP66

### Classifications

#### eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27261207
eCl@ss 8.0	27449290
eCl@ss 9.0	27440290

#### ETIM

ETIM 4.0	EC000441
----------	----------

# Corrugated tube screw connection - HC-B-GCA-M32-PLRBK - 1412022

## Classifications

ETIM

ETIM 5.0	EC000441
----------	----------

## Approvals

Approvals

---

Approvals

EAC

---

Ex Approvals

---

Approvals submitted


---

## Approval details

EAC
-----

## Drawings

Dimensional drawing



Dimensional drawing

---