

PRODUCT P/N 10039632--

FRONT PLUG HOLE SIZE	
0	.170/4.32 DIA
1	.200/5.08
2	.230/5.84
3	.260/6.60
4	.290/7.37
5	.320/8.13 DIA

FRONT PLUG COLOR	
2	OFF WHITE
4	BLACK
7	SILVER GRAY
9	PEBBLE GRAY

CAP HOLE SIZE REF	
0	.170/4.32 DIA
1	.200/5.08
2	.230/5.84
3	.260/6.60
4	.290/7.37
5	.320/8.13 DIA

CAP COLOR	
2	OFF WHITE
4	BLACK
7	SILVER GRAY
9	PEBBLE GRAY

CRIMP RING INSIDE DIA	
1	.2150/5.461 DIA
2	.1700/4.318 DIA
3	.2600/6.604 DIA
4	.1400/3.556 DIA
5	.1900/4.826 DIA
6	.3200/8.128 DIA
7	.2900/7.366 DIA
8	.2350/5.969 DIA
9	.3400/8.636 DIA

MINI LATCH HOUSING
1

SHIELD CAN
1

LEAD FREE OPTION
LF

NOTES:

- EACH KIT CONTAINS ONE EACH OF THE FOLLOWING COMPONENTS:
LATCH-N-LOK PLUG
LATCH-N-LOK CAP
STEP MINI-LATCH HOUSING
SHIELD CAN
CRIMP RING
- COMPONENTS ARE BULK PACKAGE WITH 100 PC OF A COMPONENT PER BAG. PV'S MUST BE ORDERED SEPARATELY.
- MATERIALS USED: PLUGS AND CAPS ARE MOLDED IN POLYCARBONATE. THE STEP MINI-LATCH HOUSING IS MOLDED IN NYLON, COLOR BLACK THE CRIMP RING IS 304 STAINLESS STEEL, 1/2 HARD. THE SHIELD CAN IS 1/2 HARD BRASS, PLATED WITH 100-150 μ "/2.54-3.81 μ OF PURE TIN.
- PLUGS, CAPS, MINI-LATCH HOUSING AND SHIELD CANS ARE ALL U.L. RECOGNIZED AND CSA APPROVED COMPONENTS.
- ⑤ PLUG AND CAP COLORS LISTED ARE LOW GLOSS FINISH.
- ⑥ THESE KITS DO NOT INCLUDE PV TERMINALS.
- ⑦ ADD LF SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION.
- IF "LF" P/N THE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.



FCIconnect.com

Copyright FCI

mat'l. code		surface		tolerance		projection		product family	
-		ISO 1302		ISO 406		ISO 1101		LATCH-N-LOK	
ltr		ecn		no		dr		date	
A									
		angles		linear		.xx ±.01/.3		INCH/MM	
						.xxx ±.005/.13		2X10 SPECIAL PLUG CONNECTOR	
		σ±2'				.xxxx ±.0020/.051		KIT W/O PV'S	
		dr		M.HERNANDEZ		9/20/06		dwg no	
		enr		M.BARRIOS		9/20/06		sheet 2 of 2 size	
		chr		M.BARRIOS		9/20/06		10039632 A3	
		appd		M.BARRIOS		9/20/06		type Product Customer Drawing	
sheet index		revision sheet							

form: A3