











NOTE
 MATERIAL
 INSULATOR: PBT (UL94V-0)
 CONTACTS: PHOSPHOR BRONZE
 SHELL: BRASS
 SHELL: SPCC
 CONTACT PLATING: GOLD PLATING OVER NICKEL
 ELECTRICAL SPECIFICATION
 CURRENT RATING: 5AMP;
 CONTACT RESISTANCE: 30mΩ MAX.
 INSULATION RESISTANCE: 1000MΩ MIN 500V DC.
 DIELECTRIC WITHSTANDING VOLTAGE: 5000V AC ENVIRONMENTAL
 OPERATING TEMPERATURE: -55°C~105°C.
 PART NO. DESCRIPTION:



| | | | | | | | | | |
|--|-------|---------|--|--------|------------|--------|-------|----------------------------|-------|
| 10/04/02 | ING | | NEW DWG | | AO | | | | |
| DATE | DR.BY | ECN.NO. | DESCRIPTION | MARK | VER. | | | | |
| -TOLERANCES- UNLESS OTHERWISE SPECIFIED | | | <h1 style="text-align: center;">CnC Tech , LLC</h1> <div style="display: flex; justify-content: center; align-items: center;"> </div> <p style="text-align: center;">TITLE: MICRO USB 3.0 MICRO ASSEMBLY TYPE B/MALE 10P</p> | | | | | | |
| X.X | ±0.38 | X.X° | | | | ±3.00° | APPD: | PRODUCT NO: 1003-026-22300 | |
| X.XX | ±0.25 | X.XX° | ±1.00° | CHECK: | DATE | SCALE | UNIT | TYPE | PAGE |
| X.XXX | ±0.13 | X.XXX° | ±0.05° | DRAW: | 2010.04.02 | 1:1 | mm | Z | 1 / 1 |