




UNIT:mm



CABLE WHITE PRINT
 USB CABLE E189529 AWM AWM 2725 28AWG/1PR AND
 24AWG/2C 80C 30V VW-1

PIN ASSIGNMENT:



Electrical test:
 1. 100% short, open, miswire test
 2. Conduct resistance: 2 Ohm(max)
 3. Insulation resistance: 5Mohm(min)
 4. dielectric test: DC 300V

⑧	PE BAG	1/10	CLEAR SIZE: 230*300*0.05mm PRINT BLACK "MADE IN CHINA" + "10PCS".
⑦	PE BAG	1	CLEAR SIZE: 100*200*0.05mm PRINT BLACK "MADE IN CHINA" + "1PC"
⑥	TIE	1	BLACK L=80mm
⑤	OUT JACKET	6g	BLACK PVC-40P (MOULD NO.: MW-65)
④	OUT JACKET	6g	BLACK PVC-40P (MOULD NO.: MW-40)
③	CABLE	1	BLACK USB1. 1 U12725 28#/1P+24#/2C+AEB OD: 4.7mm L=1000±10mm
②	CONN	1set	USB B MALE SHELL: NICKEL. PIN G/F 3PCS TYPE INSULATOR COLOR: WHITE
①	CONN	1set	USB A MALE SHELL: NICKEL. PIN G/F 4PCS TYPE INSULATOR COLOR: WHITE
NO.	NAME	QTY	SPECIFICATION

CNC Tech, LLC
 Industrial Cable and Connector Technology

DRAWN	ZHONGHS	DRAWING NO	
CHECKED		CUSTOMER	
APPROVAL		ITEM NO.	101-1030-BL-00100
DECIDED		DATE	2012-02-15
VERSIONS/EDITION	A/0	PROJECTION	